INCHEM POLONIA

TECHNICAL DATA SHEET

MIXSTONE PROFESSIONAL VARNISH

English translation prepared from official Inchem source material. Original source indicates update date 22.04.2024, version 2.0/EU.

Key features

- Painting and renovation
- Excellent coverage
- Colour fastening
- Fast drying
- UV protection

Basic product information

Colour: Black, Silver, Gold
Effect: Satin
Capacity: 80 ml, 300 ml

Description

MIXSTONE PROFESSIONAL VARNISH is a high-quality product designed for professional use both indoors and outdoors. Its formula is based on water, acrylic resin and effect pigments, which helps deliver durability and attractive decorative results. It has very good adhesion to a wide variety of substrates, making it suitable for painting and renovating letters on tombstones and for creating decorations and patterns on stone substrates such as marble, granite, sandstone and terrazzo. The lacquer forms a coating resistant to scrubbing and scratches, providing a long-lasting aesthetic effect. It is also waterproof and resistant to weather conditions, so it retains its properties even in challenging outdoor environments. An additional advantage is its neutral smell, which makes application more comfortable for the user. MIXSTONE PROFESSIONAL VARNISH offers both surface protection and the ability to create beautiful, durable decorations on a variety of stone materials.

How to use

1. The surface to be painted should be dry, clean and free from grease. Before painting, remove all dirt, greasy stains and remnants of old coatings.
2. Mix the product thoroughly immediately before painting. Do not dilute. Always carry out a test on the substrate first.
3. Apply with a brush, roller or sponge. Stir the varnish frequently during painting.
4. Depending on the desired effect, apply 1 or 2 coats.
5. Drying time is approximately 2 hours and depends on conditions at the place of application, especially temperature and humidity.

Additional information

- Optimal application conditions: temperature from +10°C to +30°C and relative humidity below 70%.
- Initial surface protection is achieved after 24 hours. The coating reaches full durability after 7 days. Until then, do not clean the painted surface and protect it from water, dirt and mechanical damage.
- Wash tools with water and detergent immediately after painting.

- Coverage: up to 10 m²/l depending on the type of substrate and application method. Stated coverage is for one coat.
- Number of layers: 1 to 2 coats, depending on the substrate and the desired effect.
- Shelf life: 36 months from the date of production. Once opened, use within 6 months.
- Transport and storage: store and transport in sealed original packaging at temperatures from +5°C to +40°C. Protect from frost.
- Keep out of reach of children.
- If swallowed, consult a doctor.
- VOC content limit (cat. A/d/WB): 130 g/l. Product contains max. 130 g/l.
- Contains 1,2-benzisothiazol-3(2H)-one. May cause an allergic reaction.
- Detailed safety information is provided on the product packaging and in the Safety Data Sheet.

Manufacturer disclaimer

The data in this technical data sheet is based on laboratory tests and practical experience and is provided to the best of the manufacturer's knowledge in order to support optimal use of the product. This information does not constitute a basis for the legal liability of the manufacturer, as the manufacturer has no control over the conditions in which the product is used. The manufacturer reserves the right to change the information contained in the technical data sheet without prior notice to the customer.

Manufacturer

INCHEM POLONIA Ltd.
Poland, 92-612 ■ód■, 18 Bartnicza Street
tel.: +48 603 937 760
email: biuro@inchem.pl
NIP: PL 728 273 94 05; Identification number: 100811758

Prepared for use on Decomin.ie as an English-language reference document.