INCHEM POLONIA | TECHNICAL DATA SHEET

DEKOR Decorative Varnish | Version 5.1/PL | Updated: 12 August 2025

English translation of the original Polish technical data sheet. Translation prepared for Decomin Paints Ireland; the Polish source remains authoritative.

Product features

Protects and decorates; excellent coverage; long-lasting colour; fast drying; UV protection.

Colours: White, Black, Pearl, Silver, Antique Gold, Gold **Effect:** Satin **Volume:** 80 ml

Product description

DEKOR Decorative Varnish is an innovative product formulated with water-based acrylic resin and special effect pigments. Carefully selected ingredients give the varnish high durability and resistance to outdoor conditions, making it suitable for interior and exterior use. Its excellent adhesion to different substrates allows use on stone, metal, glass, paper, wood, leather and plastic, and for painting lettering on gravestones. The coating is resistant to scrubbing, waterproof and weather-resistant, helping maintain an attractive long-lasting finish even in demanding outdoor conditions. It also has a neutral odour. DEKOR is intended for decorative applications requiring both aesthetic appeal and surface protection.

Directions for use

• The surface to be painted must be dry, clean and degreased. Remove all dirt, grease stains and remnants of old coatings before painting.

• Mix the product thoroughly immediately before painting. Do not dilute. Always test the product on the substrate first.

• Apply using a brush, roller or sponge. Stir the varnish frequently during application.

• Apply 1 or 2 coats, depending on the desired effect.

• Drying time is approximately 2 hours, depending on the conditions at the application site (temperature and humidity).

Additional information

• Optimal conditions: +10°C to +30°C and relative air humidity below 70%.

• Initial surface protection after 24 hours. The coating reaches full strength after 7 days. Until then, do not clean the painted surface; protect it from water, dirt and mechanical damage.

• Clean tools with water and detergent immediately after painting.

Coverage and coats

Coverage: Up to 10 m²/litre, depending on substrate and application method. The stated rate is for one coat.
Number of coats: 1 to 2, depending on the substrate and desired effect.

Shelf life

36 months from date of manufacture. Once opened, use the contents within 6 months.

Transport and storage

Store and transport in tightly sealed original packaging at temperatures between +5°C and +40°C. Protect from freezing.

Notes and safety

• Keep out of reach of children.

• If swallowed, consult a doctor.

• VOC content limit (category A/d/FW): 130 g/l. The product contains a maximum of 130 g/l.

• Contains 1,2-benzisothiazol-3(2H)-one. May cause an allergic reaction.

• Detailed safety information is given on the product packaging and in the Safety Data Sheet.

Manufacturer statement

The data in this technical sheet are based on laboratory tests and practical experience and are provided to the best of the manufacturer’s knowledge to ensure optimum use of the product. They do not constitute a basis for the manufacturer’s legal liability, since the manufacturer cannot influence or control application conditions. The manufacturer reserves the right to change the information in this sheet without prior notice to the customer.

INCHEM POLONIA Sp. z o.o. | ul. Bartnicza 18, 92-612 ■ód■, Poland | +48 603 937 760 | biuro@inchem.pl | NIP: PL 728 273 94 05 | REGON: 100811758